

| Model: | Item #: | Date: |
|----------|---------|----------------|
| | | |
| Projects | Otv | Annuaried Divi |

Stationary Gas Connector

Gas Connectors



Standard Features

- For use on Stationary Commercial Gas Appliances only
- Durable steel swivel fittings
- Antimicrobial yellow coating
- Stainless steel construction
- Variable lengths and interior diameters available
- 0.5 PSI maximum operation pressure
- Suitable for indoor and outdoor use
- Safe & easy installation
- 5 year warranty

| Model | I.D. | Length | BTU/hr. Flow * | Includes | Packed In |
|---------|------|--------|----------------|--|-----------|
| S7536 | 3/4" | 36"L | 256,000 | Gas Connector | Poly Bag |
| S7536B | 3/4" | 36"L | 256,000 | Gas Connector | Color Box |
| S7536K | 3/4" | 36"L | 256,000 | Gas Connector, (2) 90° Elbows, Gas Valve | Color Box |
| S7536K1 | 3/4" | 36"L | 256,000 | Gas Connector, (2) 90° Elbows | Color Box |
| S7548 | 3/4" | 48"L | 225,000 | Gas Connector | Poly Bag |
| S7548B | 3/4" | 48"L | 225,000 | Gas Connector | Color Box |
| S7548K | 3/4" | 48"L | 225,000 | Gas Connector, (2) 90° Elbows, Gas Valve | Color Box |
| S7548K1 | 3/4" | 48"L | 225,000 | Gas Connector, (2) 90° Elbows | Color Box |

^{*} This connector meets or exceeds time minimum allowable capacity as determined under test conditions specified in ANSI Z21.24 CSA 6.10. Straight Length Capacity - BTU/hr), 0.64 SP. GR. @ 0.5 inch Water Column (125 Pa) Pressure Drop. 1,000 BTU Per cubic ft. (37.2 MJ Per cubic meter)

Durable Steel Swivel Fittings

 Heavy duty swivel fittings are corrosion-resistant and extends connector longevity

Antimicrobial Yellow Coating

 PVC protective coating applied for added strength and durability

Stainless Steel Construction

 304 stainless steel tubing provides flexibility and versatility during installation



Product Compliance

ANSI Z21.24-22CSA 6.10-22





Learn more at krowne.com/warranty

Warning:

Stationary gas connectors are designed for occasional movement after installation of stationary or fixed appliances only. Repeated bending, flexing, torsion or excessive vibration must be avoided. Normal operation of a clothes dryer, rooftop HVAC unit or similar gas appliance does not constitute extreme vibration or movement.

Stationary Gas Connectors are NOT to be installed on Moveable Commercial Gas Appliances. Product mishandling and/or misuse will void warranty.

Connections should be made by qualified personnel who will observe all applicable safety codes.

Stationary gas connectors are not to be installed on moveable commercial gas appliances. Product mishandling and/or misuse will void warranty.

California Prop 65 Warning:

This product can expose you to chemicals including lead and lead compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.